

**DIN  
SMF**

**EUROPEAN CARS**

CODE	DIN GROUP	BCI GROUP	VOLTAGE	C20	C5	RC	A EN (-18°C)	CA (0°C)	HCA (22°C)	SAE (-18°C)	LENGHT	WIDHT	HEIGHT	LAYOUT	TERMINAL TYPE	HOLD DOWN	HOLD DOWN (BCI)
RSMF360	L1B	99R	12	36	29	54	300	360	400	330	207	175	175	0	1	B13	24
RSMF440	L1		12	44	35	68	400	460	510	430	207	175	190	0	1	B13	
RSMF450	L1		12	45	36	70	400	460	510	430	207	175	190	0	1	B13	
RSMF451	L1B	99R	12	45	36	70	400	460	510	430	207	175	175	0	1	B13	24
RSMF452	L2B	90	12	45	36	70	400	460	510	430	242	175	175	0	1	B13	24
RSMF500	L1		12	50	40	79	460	520	600	500	207	175	190	0	1	B13	
RSMF501	L2	47	12	50	40	79	460	520	600	500	242	175	190	0	1	B13	24
RSMF550	L2	47	12	55	44	88	510	580	640	560	242	175	190	0	1	B13	24
RSMF551	L2B	90	12	55	44	88	510	580	640	560	242	175	175	0	1	B13	24
RSMF600	L2	47	12	60	48	98	540	620	700	580	242	175	190	0	1	B13	24
RSMF601	L2B	90	12	60	48	98	540	620	700	580	242	175	175	0	1	B13	24
RSMF660	L3	48	12	66	53	110	560	650	720	610	278	175	190	0	1	B13	24
RSMF661	L3B	91	12	66	53	110	560	650	720	610	278	175	175	0	1	B13	24
RSMF720	L3	48	12	72	58	122	600	700	760	640	278	175	190	0	1	B13	24
RSMF740	L3	48	12	74	59	126	640	760	820	700	278	175	190	0	1	B13	24
RSMF750	L3	48	12	75	60	128	640	760	820	700	278	175	190	0	1	B13	24
RSMF751	L3B	91	12	75	60	128	640	760	820	700	278	175	190	0	1	B13	24
RSMF880	L5	49	12	88	70	154	740	850	900	790	353	175	190	0	1	B13	24
RSMF881	L5B	93	12	88	70	154	740	850	900	790	353	175	175	0	1	B13	24
RSMF1000	L5	49	12	100	80	179	820	950	980	880	353	175	190	0	1	B13	24
RSMF1001	L5B	93	12	100	80	179	820	950	980	880	353	175	175	0	1	B13	24

Reverse polarity are available for all types

