

SMF

CODE	DIN GROUP	BCI GROUP	VOLTAGE	C20	C5	RC	A EN (-18°C)	SAE (0°C)	LENGHT	WIDHT	HEIGHT	LAYOUT	TERMINAL TYPE	HOLD DOWN	HOLD DOWN (BCI)
RHDSMF1200	A(D4)		12	120	96	223	800	860	513	188	223	3	1	B00	
RHDSMF1350	A(D4)		12	135	108	256	860	930	513	188	223	3	1	B00	
RHDSMF1500	B(D5)	4D	12	150	120	290	900	970	513	223	223	3	1	B00	8
RHDSMF1650	B(D5)	4D	12	165	132	324	980	1060	513	223	223	3	1	B00	8
RHDSMF1800	B(D5)	4D	12	180	144	360	1050	1130	513	223	223	3	1	B00	8
RHDSMF2000	C(D6)	8D	12	200	160	407	1130	1220	518	276	242	3	1	B00	8
RHDSMF2100	C(D6)	8D	12	210	168	432	1150	1240	518	276	242	3	1	B00	8
RHDSMF2250	C(D6)	8D	12	225	180	468	1230	1330	518	276	242	3	1	B00	8

MF

CODE	DIN GROUP	BCI GROUP	VOLTAGE	C20	C5	RC	A EN (-18°C)	CA (0°C)	HCA (22°C)	SAE (-18°C)	LENGHT	WIDHT	HEIGHT	LAYOUT	TERMINAL TYPE	HOLD DOWN	HOLD DOWN (BCI)
RHD900	H3		12	90	72	158	600	680	780	650	324	175	227	0	1	B03	
RHD1050	H4		12	105	84	190	700	790	910	760	346	175	230	0	1	B03	
RHD1051	D2		12	105	84	190	700	790	910	760	349	175	235	0	1	B01	
RHD1100	D2		12	110	88	201	750	850	980	820	349	175	235	0	1	B01	
RHD1150	D2		12	115	92	212	800	900	1040	870	349	175	235	0	1	B01	
RHD1200	D4A		12	120	96	223	800	900	1040	870	513	189	223	0	1	B03	
RHD1350	D4A		12	135	108	256	900	1020	1170	980	513	189	223	3	1	B03	
RHD1500	B	4D	12	150	120	290	950	1070	1240	1040	513	223	223	3	1	B00	8
RHD1650	B	4D	12	165	132	324	1000	1130	1300	1090	513	223	223	3	1	B00	8
RHD1800	B	4D	12	180	144	360	1100	1240	1430	1200	513	223	223	3	1	B00	8
RHD2000	C	8D	12	200	160	407	1150	1300	1500	1250	518	276	242	3	1	B00	8
RHD2100	C	8D	12	210	168	432	1150	1300	1500	1250	518	276	242	3	1	B00	8
RHD2250	C	8D	12	225	180	468	1200	1360	1560	1310	518	276	242	3	1	B00	8
RHD2400	C	8D	12	240	192	505	1200	1360	1560	1310	518	276	242	3	1	B00	8

SHD

RHD1800	B	4D	12	180	144	360	1100	1240	1430	1200	513	223	223	3	1	B00	8
RHD2000	C	8D	12	200	160	407	1150	1300	1500	1250	518	276	242	3	1	B00	8
RHD2100	C	8D	12	210	168	432	1150	1300	1500	1250	518	276	242	3	1	B00	8
RHD2250	C	8D	12	225	180	468	1200	1360	1560	1310	518	276	242	3	1	B00	8
RHD2400	C	8D	12	240	192	505	1200	1360	1560	1310	518	276	242	3	1	B00	8

Reverse polarity are available for all types



*Maximum performance with special fiber-reinforced separators

» www.rodsons-battery.com