

MAGNA M-SKID2/ M-SKID4

The **Magna M-SKID2** has a wide lug tread pattern that provides optimal grip and traction on both smooth and rough surfaces. This pattern offers an extended tyre life due to its reinforced sidewall and strong nylon casing.

The **Magna M-SKID4** is designed for maximum performance on concrete, asphalt and other hard surfaces. The extra-deep, aggressive patterns is especially for skid steer loaders. The full-flat profile with self-cleaning stepped tread improves performance.



The deep tread and special traction pattern improves performance and has excellent self-cleaning properties.



All cross ply construction with an improved load performance and enhanced operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre Size	Pattern	Tyre type	PLY rating	Max speed (km/h)	Load speed index	Single max. load/ pressure	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Rim
5.70-12	M-SKID2	TL	8	10	101A2	835 kg/ 6.2 bar	570	146	13	4.50
23X8.50-12	M-SKID2	TL	8	10	106A2	960 kg/ 4.5 bar	574	213	13	7.00
27X8.50-15	M-SKID2	TL	10	10	115A2	1200 kg/ 4.8 bar	660	216	15	7.00
10-16.5	M-SKID2	TL	10	10	134A2	2135 kg/ 5.2 bar	773	264	22	8.25
12-16.5	M-SKID2	TL	12	10	145A2	2865 kg/ 5.5 bar	831	307	22	9.75
14-17.5	M-SKID2	TL	14	10	155A2	3875 kg/ 5.5 bar	921	349	22	10.50
15-19.5	M-SKID2	TL	14	10	160A2	4565 kg/ 4.85 bar	1019	389	29	11.75
445/65-22.5	M-SKID-2	TL	18	40	168A2	5600kg/6.9 bar	1172	547	27	14.00
10-16.5	M-SKID4	TL	10	10	134A2	2135 kg/ 5.2 bar	773	264	35	8.25
12-16.5	M-SKID4	TL	12	10	145A2	2865 kg/ 5.5 bar	831	307	35	9.75
14-17.5	M-SKID4	TL	14	10	155A2	3875 kg/ 5.5 bar	921	349	38	10.5
15-19.5	M-SKID4	TL	14	10	160A2	4565 kg/ 4.85 bar	1019	389	38	11.75