

## MAGNA MB100/ MB210

The **Magna MB100** was specifically engineered for mobile excavators in construction applications. Its self-cleaning open tread with mud breakers makes for increased traction. The tyre offers both favorable stability and wear resistance.

The **Magna MB210** is a tough grader tyre design, developed specifically to withstand rough terrain. Applicable on soft, muddy and sandy terrain, this tyre offers both excellent self-cleaning and traction performance.



Enhanced performance due to aggressive traction pattern with excellent self cleaning properties.



All cross ply construction with an improved load performance and enhanced operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre Size	Pattern	Tyre type	PLY rating	Max speed (km/h)	Load speed index	Single max. load/ pressure	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Rim
10.00-20	MB100	TT	16	50	146B	3000 kg/ 7.5 bar	1055	278	22	7.50
13.00-24	MB210	TL	12	40	143A8	2725 kg/ 3.0 bar	1280	335	25	8.00TG
				10	168A2	5600 kg/ 4.5 bar				
14.00-24	MB210	TL	16	40	153A8	3650 kg/ 3.5 bar	1350	360	29	8.00TG
				10	177A2	7300 kg/ 5.5 bar				
16.00-24	MB210	TL	16	40	160A8	4500 kg/ 3.0 bar	1460	435	29	10.00VA
				10	181A2	8250 kg/ 4.25 bar				