

PORT HANDLING

MAGNA MB300/MB300+

IND-3 (E3/L3)

The Magna MB300 is a multi-functional tyre designed for container handling equipment at ports and terminals. The wide tread improves mobility and offers a more comfortable ride with excellent heat-resistance and wearing performance.

The Magna MB300+ has a sturdy carcass structure design, fully suitable for heavy torque and heavy loads on port mechanical vehicles. The unique compound used for this E4 pattern gives the tyre a long original tread life and advanced cut-resistance, as well as protection against overheating.



Improved traction and performance through deep nondirectional tread design.



All cross ply construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.





Tyre size	Pattern	TT/TL	Ply Rating	Tra code	Max. speed (km/h)	Pressure (kpa)	Loading capacity (kg)	0.D. (mm)	S.W. (mm)	Tread depth (mm)	Rim	Weight (kg)
14.00-24	MB300	TT	28	E3/L3	25	925	10000	1370	375	26	10.00	120
14.00-24	MB300+	TT/TL	28	E4	25	1000	12000	1370	375	30	10.00	140
15.5-25	MB300	TT/TL	12	E3/L3	25	400	5600	1275	395	25	12.00/1.3	90