

## MAGNA MB400/ MB410

### IND

The **Magna MB400** is specially designed for backhoe- and compact wheel loaders. Reinforced sidewall and strong nylon casing provide superior strength and a longer tread life.

The **Magna MB410** features a modified tread pattern for excellent traction and flotation in soft underfoot conditions. The tread design is optimized with self-cleaning mud breakers with a wear and cut resistant compound.



The deep tread and special traction pattern improves performance in demanding offroad conditions.



All cross ply construction with an improved load performance and enhanced operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre Size	Pattern	Tyre type	PLY rating	Max speed (km/h)	Load speed index	Single max. load/pressure	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Rim
10.5/80-18	MB400	TL	14	30	125A6 IND	1650 kg/ 4.9 bar	881	274	25	W9
12.5/80-18	MB400	TL	16	30	135A6 IND	2180 kg/ 4.9 bar	975	295	25	W9
17.5L-24	MB410	TL	12	40	146A8 IND	2995 kg/ 2.6 bar	1241	445	27	15.00
19.5L-24	MB410	TL	12	40	151A8 IND	3450 kg/ 2.3 bar	1314	495	30	17.00
18.4-26	MB410	TL	12	40	156A8 IND	4000 kg/ 2.5 bar	1426	467	29	16.00
16.9-24	MB410	TL	14	40	151A8 IND	3670 kg/ 3.3 bar	1309	429	26	15.00
16.9-28	MB410	TL	14	40	142A8 IND	2670 kg/ 2.7 bar	1410	429	28	15.00