

MAGNA MB01/ MB01S

IND-4 (E4)

The **Magna MB01** is suitable for harbor equipment such as container handlers and reachstackers. Developed with a highly wear resistant tread compound to avoid tread cracks and for excellent performance and an extended tyre lifecycle.

The **Magna MB01S** offers large carrying capacity, special compounding and a construction designed for high air-pressured and shock loads typical in port situations.



Improved traction and performance through non-directional E3 tread design.



All cross ply construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	Ply rating	Tra code	Max. speed (km/h)	Single max. load (kg)				Pressure (kPa)	O.D. (mm)	S.W. (mm)	Tread depth (mm)	Rim	Weight (kg)
					Static	5 km/h	10 km/h	25 km/h						
16.00-25	MB01	32	E3	25	22500	18100	16900	15600	1000	1495	430	32	11.25/2.0	197
18.00-25	MB01	40	E4	25	31500	25400	23600	21900	1000	1675	500	55	13.00/2.5	399
21.00-25	MB01	40	E3	25	36400	29300	27300	25300	1000	1750	575	38	15.00/3.0	396
18.00-33	MB01	40	E4	25	37000	29900	27800	25700	1000	1875	500	65	13.00/2.5	511
21.00-35	MB01	40	E3	25	43700	35200	32800	30400	1000	2005	570	38	15.00/3.0	516
18.00-25	MB01S	40	E4s	25	31500	25400	23600	21900	1000	1675	515	60	13.00/2.5	405