



**ALL STEEL RADIAL
CONSTRUCTION
MULTIFUNCTIONAL**

MINING & EARTHMOVER


MAGNA MA01+ E3/L3

The Magna MA01+ is designed to be a multi-purpose tyre, ideal for use on wheel loaders, dozers, scrapers, graders and articulated dump trucks operating in soft surfaces.

Wide flat footprint for maximum stability and wear. The heat resistant rubber compound improves productivity and reduces operating costs.



Aggressive E3/L3 non-directional tread pattern provides superior traction in soft underfoot.



All steel radial construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	Load symbol	Tra code	Max. speed (km/h)	Load/speed index	Single max. load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Tyre weight (kg)
17.5R25	MA01+	**	E3	50	167B	5450 kg/5.25 bar	14.00/1.5	1350	445	27	153
			L3	10	182A2	8500 kg/6.5 bar					
20.5R25	MA01+	**	E3	50	177B	7300 kg/5.25 bar	17.00/2.0	1490	520	33	235
			L3	10	193A2	11500 kg/6.5 bar					
23.5R25	MA01+	**	E3	50	185B	9250 kg/5.25 bar	19.50/2.5	1615	595	36	316
			L3	10	201A2	14500 kg/6.5 bar					
26.5R25	MA01+	**	E3	50	193B	11500 kg/5.25 bar	22.00/3.0	1750	675	37	439
			L3	10	209A2	18500 kg/6.5 bar					
29.5R25	MA01+	**	E3	50	200B	14000 kg/5.25 bar	25.00/3.5	1875	750	43	599
			L3	10	216A2	22400 kg/6.5 bar					