



## MAGNA MAO3

**E2** 

The Magna MA03 is designed with a universal tread pattern to help minimize fuel consumption, improve traction and deliver a more comfortable ride.

This crane tyre features excellent wear resistance, exceptional operator comfort and durability in high-speed and demanding on- and offroad applications.



The aggressive, self-cleaning tread design provides excellent traction in severe off-road conditions.



All steel radial construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.





Tyre size	Pattern	Tra code	Load symbol	Load/Speed Index	Single max load/pressure	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Rim	Tyre weight (kg)
385/95R24	MA03	E2	***	170 E	6000 kg/10 bar	1364	396	25	10.00W	133
385/95R25	MA03	E2	***	170 F	6000 kg/10 bar	1364	396	25	10.00/1.5	138
445/95R25	MA03	E2	***	174 F	6700 kg/9.0 bar	1488	432	26	11.25/2.0	211
525/80R25	MA03	E2	**	176 F	7100 kg/7.0 bar	1498	533	31	17.00/2.0	232
505/95R25	MA03	E2	***	186 E	9500 kg/10.0 bar	1585	505	26	13.00/2.5	325