

MAGNA MB800

The MB800 is a pneumatic tyre for forklifts and other industrial material handling purposes. The special compound ensures the wear and puncture resistance, giving the tyre a long service life.

The low rolling resistance of the Magna MB800 saves the fuel consumption. This pattern is designed for pneumatic tyre ride while delivering the benefits of a solid pneumatic tyre.



Self-cleaning and non-directional tread pattern.



All cross ply construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Load capacity (kg)

Tyre size	Pattern	Ply Rating	Load capacity (kg)				O.D. (mm)	S.W. (mm)	Tread depth (mm)	Rim	Tyre weight (kg)
			Drive wheel kg @ 25 km/h	Steer wheel kg @ 25 km/h	Drive wheel kg @ 35 km/h	Steer wheel kg @ 35 km/h					
5.00-8	MB800	10	1150	970	1065	850	470	137	11	3.50	7
6.00-9	MB800	10	1505	1275	1400	1120	540	160	12	4.00	11
6.50-10	MB800	12	1895	1600	1765	1410	590	175	13	5.00	14
7.00-12	MB800	14	2590	2190	2405	1925	676	190	14	5.00	19
8.25-15	MB800	14	3775	3185	3505	2800	840	235	18	6.50	32
28x9-15	MB800	14	3050	2575	2835	2265	710	220	18	7.00	26
250-15	MB800	18	4110	3470	3820	3050	735	250	18	7.50	34
300-15	MB800	20	5940	4990	5485	4375	840	300	20	8.00	51
10.00-20	MB800	20	6950	5800	6500	5150	1074	277	22	7.50	75
12.00-20	MB800	20	7750	6510	7207	5735	1145	315	24	8.50	86
12.00-20	MB800	24	8500	7140	7905	6290	1145	315	26	8.50	TBA